

FlashRunner Series Comparison Table



DC10213

Features	FlashRunner I Series					FlashRunner II Series	FlashRunner III Series	FlashRunner Quattro Series	FlashRunner FR3070A
	FR01ENG	FR01LAN	FR01ATO	FR01M01	FR01PRO				
Programming Support	Universal	Universal	Universal	Universal	Universal	One Manuf.	One Manuf.	Universal	Universal
Host Interface(s)	RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	RS-232	LAN, RS-232	LAN, RS-232
ISP Sites	1	1	1 (Switchable to ATE)	8 (Multiplexed)	1	1	1	4 (Parallel) Up to 16 (Mult.)	1
ISP Connector Type	Header	D-Sub	DIN 41612	Header	D-Sub	D-Sub	D-Sub	DIN 41612	Header
Power Supply	9-24V DC	9-24V DC	9-24V DC	9-24V DC	110/220V AC	9-24V DC	7.5V DC	9-18V DC	12V DC
SD Card (FAT16, up to 2GB)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Logs/Reports	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
On-Board Dynamic Memory	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	-	512 Bytes	512 Bytes
IP Piracy Protection	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
Scripts (Host Mode)	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Scripts (Standalone Mode)	32	32	32	32	32	32	1	32	-
Dimensions (mm)	130 x 74 x 27	130 x 74 x 43	130 x 74 x 43	130 x 74 x 43	360 x 210 x 45	130 x 74 x 43	90 x 65 x 35	180 x 155 x 55	152 x 75 x 13
Real-Time Clock/Calendar	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	No
Optoisolation	Yes	Yes	Yes	Yes	Yes	Yes	No	FR04A08 Only	No